

JILONG
Since 1993



Optical Attenuator

OVA-33



5000mAh High-capacity Battery



RJ45: Wire sequencing



Customizable Calibration Wavelengths



4.3-inch Touch Screen



Handheld, Compact and Light



Lighting

OVA-33 Optical Attenuator



Optic Attenuator is a passive device used to reduce optical signal power. It achieves power adjustment by absorbing, scattering, or reflecting light energy. Its primary applications include preventing receiver overload, balancing optical power across multiple channels, and simulating long-distance transmission loss.


Maximum Attenuation



Maximum Attenuation **40dB/80dB**

Attenuation Resolution **0.01dB**

Calibration Wavelength



Calibration Wavelength **1310/1550** (nm) Customization Available

RJ45 Wire sequencing


Ensure precise wire sequencing. Design of signal transmission interface plug-and-play to avoid loss.



4.3-inch Capacitive Touch HD Screen



Application scenarios



5000mAh High-capacity Battery



Built-in lighting for easier operation




Type-C Charging



All-Body Shock-Absorbing Rubber Casing



SC (Standard Configuration)



Product Configuration

① Carrying Casex1

② OVA-43x1

③ Power Cord x1

④ RJ45 Remote Module x1

⑤ Shoulder Strap x1



Product Display



Front



Back



- wavelength switching
- Homepage
- Power on/off(long press)/Lighting(short press)



Parameters

Attenuator Parameters

Calibration Wavelength	1310/1550 (nm)	
Peak Attenuation	40dB	80dB
Insertion Loss	≤2dB	
Resolution Ratio	0.01dB	
Attenuation Error	±0.2dB	
Repeatability	±0.1dB	
Maximum Input Power	24dBm	
Working Temperature	-10~+50 (°C)	
Storage Temperature	-20~+60 (°C)	
Automatic Shutdown Time	10min	

RJ45 Networks Test

Wavelength (nm)	CAT5、CAT6
Distance of Cable Collationl:	300m
Distance of emitting signal:	300m

General Parameters

Language	English, Chinese, Spanish, French, Portuguese, Russian, Thai, Korean
Optical Fiber Port	SC/UPC
Display Screen	4.3-inch color LCD display screen
Port	Charging port x 1, USB 2.0 x 1, RJ45 x 1
Working Temperature	-10 – 50 °C (0–40 °C for use with power, 0 to 35 °C battery charging)
Storage Temperature	-20 to 60 °C
Height	4000 m
Humidity	0 to 90% RH
Power Mode	5V, 3A(DC adapter)
Battery	3.7V,5000mAh,≥18.5Wh
Lighting	Light Intensity>15000mcd
Data Storage	Memory: 1000 power measurement records External Storage: USB
Size	179 mm (W) × 112 mm (H) × 48 mm (D)
Weight	0.6 kg (Unit + Battery)

Note: All specifications are based on measurements with a new battery at 23°C ± 2°C.

Contact us

Nanjing Jilong Optical Communication Co., Ltd

Add: No. 8, Huyue East Road, Longchi Street, Liuhe District, Nanjing, China

Web: www.JILONGOT.com

Mail: info@jilongot.com

TEL: +86 400 883 6695



Focus on official
website for more