JILONG
Since 1993

VFL-22 MINI

Visual Fault Locator



MiNi
Compact

SC
FC
ST
2.5mm universal

LED light

- Pocket size design,mini and compact
- Rubber dustproof cover
- Testing distance is up to 25km,high stability
- 2.5mm universal connector,suitable for SC/ST/FC connector
- Strong and stable light source, strong penetrating power
- Be equipped with LED light,more convenient to work in the dark

Products Features



Testing distance is up to 25km



2.5mm universal connector



Products display









Products specification

Instrument Model	VFL-22-10	VFL-22-20	VFL-22-30
Power Range	10mW	20mW	30mW
Test Distance	5-8km	12-15km	20-25km
Wavelength Range	650nm		
Laser Type	LD		
Modulation Frequency	CW / 2Hz		
Operating Temperature	-20 ~ +60 (℃)		
LED Flashlight	Supported		
Power Supply	2 × AAA 1.5V batteries		
Dimensions	120 x 35 x 20 (mm)		
Weight	50g (including batteries)		

* All data above were obtained under laboratory conditions at 20°C

Contact us

Nanjing Jilong Optical Communication Co., Ltd

Add: No. 8, Huyue East Road, Longchi Street, Liuhe District, Nanjing, China

Web: www.JILONGOT.com

Mail: info@jilongot.com

TEL: +86 400 883 6695

Visit our official website for more